



Heat Shrinkable Termination Kits

Product Code : CXO-E-1112

Electrical Specifications (12 KV Rated Accessories)		
Test Requirement	Requirement Test Value	CXO/E-1112-Series
A.C. Withstand, 1 Minute	35 KV	Pass
D.C. Withstand, 15 Minute	48 KV	Pass
Discharge Extinction Voltage (<5Pc)	12.7 KV	> 12.7 KV
Impulse Withstand (Crest KV)	75 KV	> 75 KV
Continuous Current Rating	As Per Cable	As Per Cable

Ordering Information		
Cable Size (Sq mm)	Outdoor Kit Code	Indoor Kit Code
16-35	CXO-11	CXE-11
50-95	CXO-12	CXE-12
120-185	CXO-13	CXE-13
240-300	CXO-14	CXE-14
400-500	CXO-15	CXE-15

[Send Enquiry](#)



Electrical Specifications (24 KV Rated Accessories)		
Test Requirement	Requirement Test Value	CXO/E-1524-Series
A.C. Withstand, 1 Minute	50 KV	Pass
D.C. Withstand, 15 Minute	96 KV	Pass
Discharge Extinction Voltage (<5Pc)	25.4 KV	> 25.4 KV
Impulse Withstand (Crest KV)	125 KV	125 KV
Continuous Current Rating	As Per Cable	As Per Cable

Ordering Information

Heat Shrinkable Termination Kits
Product Code : CXO-E-1524

Cable Size (Sq mm)	Outdoor Kit Code	Indoor Kit Code
16-50	CXO-21	CXE-21
70-120	CXO-22	CXE-22
150-185	CXO-23	CXE-23
240-400	CXO-24	CXE-24

[Send Enquiry](#)



Heat Shrinkable Termination Kits
Product Code : CXO-E-3336

Electrical Specifications (36 KV Rated Accessories)		
Test Requirement	Requirement Test Value	CXO/E-3336-Series
A.C. Withstand, 1 Minute	74 KV	Pass
D.C. Withstand, 15 Minute	144 KV	Pass
Discharge Extinction Voltage (<5Pc)	38 KV	> 25.4 KV
Impulse Withstand (Crest KV)	170 KV	170 KV
Continuous Current Rating	As Per Cable	As Per Cable

Ordering Information

Cable Size (Sq mm)	Outdoor Kit Code	Indoor Kit Code
16-50	CXO-31	CXE-31
70-120	CXO-32	CXE-32
150-185	CXO-33	CXE-33
240-400	CXO-34	CXE-34

[Send Enquiry](#)