

Heat Shrinkable Straight Through Joints Suitable for 3 core XLPE/ EPR/ PVC Insulated Cables upto 36KV



### Heat Shrinkable Straight Through Joints

Product Code : CXS-E-1236KV

Electrical Performance			
Test Requirement	12KV (6.6/6.6KV,6.36/11KV)	15-24KV (8.7/15KV,11/11KV,12.7/22KV)	36KV (19/33KV)
A.C. Withstand, 1 Minute	35 KV	50KV	75KV
D.C. Withstand, 15 Minute	48KV	96KV	144KV
Discharge Extinction Voltage (<5Pc)	12.7 KV(Min)	25.4KV(Min)	38KV(Min)
Impulse Withstand (Crest KV)	75KV(Min)	125KV	170KV(Min)
Continuous Current Rating	As Per Cable	As Per Cable	As Per Cable

Ordering Information					
12 KV		15-24 KV		36 KV	
Cable Size (Sq mm)	Kit Code	Cable Size (Sq mm)	Kit Code	Cable Size (Sq mm)	Kit Code
16-50	CXS-11	25-50	CXS-21	35-70	CXS-31
70-95	CXS-12	70-95	CXS-22	95-150	CXS-32
120-185	CXS-13	120-150	CXS-23	185-300	CXS-33
240-400	CXS-14	185-240	CXS-24	400	CXS-34
400-500	CXS-15	300-400	CXS-25		

Heat Shrinkable Straight Through Joints Suitable for PVC/ XLPE/ PILC Cables upto 3.3KV



**Heat Shrinkable Straight Through Joints**

Product Code : CXLT-CPLT

Electrical Performance		
Tests	1.1KV	3.3KV System
A.C. Voltage Withstand	3.5 KV / 5 Minute	5KV/5 Minute
D.C. Voltage Withstand	15 KV /15 Minute	20 KV/15 Minute

Cable Size (Sq mm)	Ordering Information	
	Kit Code 1.1 KV	Kit Code 3.3 KV
4 x 1.5-6	CXLT -1	CXLT -11
4 x 1.0-16	CXLT -2	CXLT -12
4 x 25-50	CXLT -3	CXLT -13
4 x 70-150	CXLT -4	CXLT -14
4 x 185-400	CXLT -5	CXLT -15